

				NZM...1		Moeller HPL0211-2007/2008		http://catalog.moeller.net	
Rated current = rated uninterrupted current				Setting range		Basic switching capacity 25 kA at 415 V 50/60 Hz		Normal switching capacity 50 kA at 415 V 50/60 Hz	
$I_n = I_u$				Overload releases		Part no. Article no.	Price see price list	Part no. Article no.	Price see price list
A				Main pole	Neutral conductor	Short-circuit releases			
				I_r	I_r	I_i			
				A	A	A			
									
Protection of systems and cables									
4 pole									
Terminals standard, terminal screws as accessories									
	20	15...20	15...20	350	NZMB1-4-A20 281237		NZMN1-4-A20 281245		
	25	20...25	20...25	350	NZMB1-4-A25 281239		NZMN1-4-A25 281247		
	32	25...32	25...32	350	NZMB1-4-A32 281241		NZMN1-4-A32 281249		
	40	32...40	32...40	320...400	NZMB1-4-A40 265799		NZMN1-4-A40 265811		
	50	40...50	40...50	300...500	NZMB1-4-A50 265801		NZMN1-4-A50 265813		
	63	50...63	50...63	380...630	NZMB1-4-A63 265803		NZMN1-4-A63 265815		
	80	63...80	63...80	480...800	NZMB1-4-A80 265805		NZMN1-4-A80 265817		
	100	80...100	80...100	600...1000	NZMB1-4-A100 265807		NZMN1-4-A100 265819		
	125	100...125	100...125	750...1250	NZMB1-4-A125 265809		NZMN1-4-A125 265821		
	160	125...160	125...160	1280	NZMB1-4-A160 281243		NZMN1-4-A160 281251		

Notes Notes for terminals → 10/47



http://catalog.moeller.net		Moeller HPL0211-2007/2008		NZM...1			
High switching capacity 100 kA at 415 V 50/60 Hz							
Part no. Article no.	Price see price list	Std. pack	Notes				

